

(1) EU-Type Examination Certificate


according to Module B Paragraph 6.1 of PPE Regulation (EU) 2016/425

- (2) Regulation of the European Parliament and of the Council of 9 March 2016 relating to personal protective equipment (PPE) - Regulation (EU) 2016/425
- (3) No. of EU-Type Examination Certificate: **ZP/B121/20** replaces no. ZP/B070/16
- (4) Product: **Anchor device type B and C**
Type: **TEMP**
- (5) Manufacturer: **INNOTECH Arbeitsschutz GmbH**
- (6) Address: **Laizing 10, 4656 KIRCHHAM, AUSTRIA**
- (7) Risk category: **III**
- (8) The design and construction of this personal protective equipment and any acceptable variation thereto are specified in the appendix to this EU type-examination certificate.
- (9) The certification body of DEKRA Testing and Certification GmbH, Notified Body No. 0158 according to Chapter V of Regulation (EU) 2016/425 of 9 March 2016, certifies that this personal protective equipment has been found to comply with the essential Health and Safety Requirements given in Annex II to the Regulation. The evaluation results are recorded in report PB 20-152. Other possibly applicable Union legislations applicable to the specified personal protective equipment have not been taken into account in this EU-type examination certificate.
- (10) The essential Health and Safety Requirements are assured in consideration of
DIN EN 795:2012 **DIN CEN/TS 16415:2017**
- (11) This EU type-examination certificate relates only to the design, examination and tests of the specified personal protective equipment in accordance to Regulation (EU) 2016/425. For category III personal protective equipment, this EU type-examination certificate may only be used in conjunction with one of the conformity assessment procedures referred to Article 19 (c).
- (12) When applying the CE Marking according to Article 16 and 17 of Regulation (EU) 2016/425 to the products that conform to the types examined, the client is obliged to add, in accordance with the attached pattern, the identification number of the Notified Body engaged in the conformity assessment according to Module C2 or D. Furthermore, the manufacturer is obliged to issue an EU declaration of conformity in accordance with Article 15 of Regulation (EU) 2016/425 and to enclose it with the personal protective equipment; or to indicate the Internet address in the manual and in the instructions in Annex II, point 1.4., at which the EU declaration of conformity can be accessed.
- (13) This EU-Type Examination Certificate is valid until **2025-07-07**

DEKRA Testing and Certification GmbH
Bochum, 2020-07-08

Signed: Kilisch
Managing director

We confirm the correctness of the translation from the German original. In the case of arbitration only the German wording shall be valid and binding.


Managing director

TRANSLATION

- (14) Appendix to
- (15) **EU-Type Examination Certificate**
ZP/B121/20
- (16) 16.1 Subject and type
Anchor device type B and C
Type: TEMP

16.2 Description

The anchor device of type B and C, type TEMP (Fig. 1) is used for the temporary protection of maximum 4 people against falls from a height. The anchor line of the anchor device is made of a wire rope (\varnothing 8 mm in the edition 7 x 7).

The anchor device is fastened to the structure at the end anchors by means of a textile strap with a ratchet brace (Fig. 2) whereas the fitting is made as a push-trough frame. The wire rope is fastened to the strap by means of an end lock type: TEMP-ENDS-10 (Fig. 4) that is fixed to the ratchet brace.

The intermediate structural anchors type: TEMP-ENDS-SZH-10 (Fig. 3) are connected to the structure by means of a strap and a ratchet brace and interconnected with an intermediate structural anchor. The anchor line is tensioned using the two strap ratchet braces connected on both sides.

The user secures himself by connecting his personal protective equipment against falls from a height to the mobile anchor point of type INNOTECH rope slider AIO GLEIT-10. The mobile anchor point is intended to pass the intermediate structural anchors and can turn around the line axis. As an alternative, the connection between the user's connector and the wire rope line can also be made using a connector in compliance with EN 362. However, then a passing of the structural intermediate anchors is not possible.

The anchor device of type TEMP is mounted horizontally to the structure onto surfaces of sufficient strength using intermediate structural anchors and end anchors and the respective straps. Bypassing the end anchors is not possible. The pre-tensioning of the flexible anchor line is 1.0 kN whereas a maximum distance of 20 m between two anchors shall not be exceeded.

The metallic components of the anchor device are made of corrosion-resistant steel.



Fig. 1: Anchor device, type: TEMP



Fig 2: End anchor points with strap and ratchet



Fig 3: Intermediate anchor type: TEMP-SZH-10



Fig. 4: Endlock, type: TEMP-ENDS-10

(17) Report

PB 20-152, 2020-07-08